

Power Runner Model 2

Universal Portable External Power Bank

■ Product Introduction

Power Runner Model 2 is a Universal Portable Power Bank which powers and charges all your portable devices. High capacity Li-Ion Cell & external power smart design with adjustable output voltage, selectable DC Plug adapters, providing you a quite convenient and better power solution for small devices that use DC Power. There are 3 types are available for further selections!

Standard Type: PR21XX

Advanced Type: PR22XX

Enhanced Type: PR23XX

□ Product Applications

It universal works with

***Digital camera**

***Camcorder**

***Portable DVD players**

***Pocket PCs**

***CD players/Walkman**

***MP3 players**

***Cell phones**

***Handheld Games**

***Flash Units**

□ Portable Power Bank

Power Runner is mobile so it goes where you go! Higher capacity to charge or powers your favorite 3C Products so as to extend longer working time and avoid insufficient power problem

□ Programmable Output Voltage

In order to fit on variety of portable electronic devices and meet with the variety of input voltages, Power Runner Model 2 has 3V,4.5V,5V,6V,7.5V,9V (see below product specification)programmable output voltage, and only by adjusting gently the voltage slide switch you may find the correct output voltage for your favorite portable

electronics.

Capacity LED Indicator

Power Runner Model 2 is also designed with four LED's to act like a fuel gauge. When all four are lit, the battery is full.

High Safety Li-Ion Cell Design

Li-ion Cell safe design enjoys no memory effect, no self-discharge, high capacity.

Over-valued Complimentary

It provides not only free 4 DC standard Plug adapters, but provides over-valued complimentary such as travel charger, Car charger, and Output wire belt-clip leather case.

Product Specification

No.	Item	Rated Performance	
1.	Output Voltage	PR21 XX	3V, 4.5V, 5V, 6V, 7.5V, 9V
		PR22 XX	
		PR23 XX	3V, 4.5V, 5V, 6V, 7.5V, 9-12V
2.	Output power	PR21 XX	10~11 Wh
		PR22 XX	18~20 Wh
		PR23 XX	36~40 Wh
3	Capacity	PR21 XX	3 V-3Ahr 4.5V-2Ahr ,5 V-1.8Ahr 6V-1.5Ahr 7.5V-1.2Ahr 9V-1Ahr
		PR22 XX	3 V-5.4Ahr 4.5V-3.6Ahr ,5V- 3.2Ahr 6V-2.7Ahr 7.5V-2.1Ahr 9V-1.8Ahr
		PR23 XX	3 V-12Ahr 4.5V-8Ahr 5V- 7.2Ahr 6V-6Ahr 7.5V-4.8Ahr 9-12 V-4Ahr
4	Input port Charging Voltage / Current	9V/800 mA	
5.	Charging Time	PR21 XX	2~3h
		PR22 XX	3~4h
		PR23 XX	7~8h
6	Capacity indicate	3 pcs. Green LED 1 pc. Red LED	
7	Output Current	2A	
8.	Car Charger input voltage	DC 11V ~ 16V	
9.	Car Charger output voltage	DC 9V ±0.2V	
10	Traveling Charger input voltage	AC 100V ~ 240V	
12	Traveling Charger	DC 9V ±0.2V	

	output voltage		
13	Operating Temperature rang	Charge 0~45°C Discharge -20~60°C	
14	Storage Temperature	-20~43°C	
15	Measurement	PR21XX	135*45*31mm
		PR22XX	135*45*31mm
		PR23XX	135*45*45.5mm
16	Weight	PR21 XX	200g
		PR22 XX	250g
		PR23 XX	350g

ACON reserves the right to change, amend, or cease the design of Power Runner. The above information is for your reference only.