

Protection Circuit Module Specifications For 16V LiFePO4 Battery Packs

Model: PCB-LFP7AS5-B

No.	Test item		Criterion
1	Voltage	Charging voltage	DC: 18V CC/CV (3.6V/1cell)
		Balance voltage for single cell	
2	Current	Balance current for single cell	
		Current consumption for single cell	≤20 μA
		Maximal continuous charging current	7A
		Maximal continuous discharging current	7A
3	Over charge Protection (single cell)	Over charge detection voltage	3.90±0.025V
		Over charge detection delay time	0.5S—2S
		Over charge release voltage	3.80±0.05V
4	Over discharge protection (single cell)	Over discharge detection voltage	2.3±0.1V
		Over discharge detection delay time	100—250ms
		Over discharge release voltage	2.0±0.05V
5	Over current protection	Over current detection voltage	0.65±0.1V
		Over current detection current	16±3A
		Detection delay time	5ms-20ms
		Release condition	Cut load
6	Short protection	Detection condition	Exterior short circuit
		Detection delay time	200-800us
		Release condition	Cut load
7	Resistance	Protection circuitry (B- TO P-)	≤50mΩ
8	Temperature	Operating Temperature Range	-40~+85°C
		Storage Temperature Range	-40~+125°C

L86*W16*T3.5mm

P+,P- = Charge+/-,Discharge+/-

