

Protection Circuit Module Specifications For 22.2V Li-ion/Li-po Battery Pack

Model: PCM-L12S35-514 (6S)

No.	Test item	Criterion	
1	Voltage	Charging voltage	DC: 25.2V CC/CV (4.2V/1cell)
		Balance voltage for single cell	4.2V±0.025V
2	Current	Balance current for single cell	85mA±5mA
		Current consumption for single cell	20 μ A
		Maximal continuous charging current	15A
		Maximal continuous discharging current	30A
3	Over charge Protection (single cell)	Over charge detection voltage	4.25±0.025V
		Over charge detection delay time	0.5S—2S
		Over charge release voltage	4.05±0.05V
4	Over discharge protection (single cell)	Over discharge detection voltage	2.5±0.07V
		Over discharge detection delay time	10—30mS
		Over discharge release voltage	3.0±0.1V
5	Over current protection	Over current detection voltage	0.2±0.015V
		Over current detection current	110±15A
		Detection delay time	5ms—20ms
		Release condition	Cut load
6	Short protection	Detection condition	Exterior short circuit
		Detection delay time	200-500us
		Release condition	Cut load
7	Resistance	Protection circuitry (B- TO P-)	30m
8	Temperature	Operating Temperature Range	-40 ~ +85
		Storage Temperature Range	-40 ~ +125

L80*W60*T20mm

