

Protection Circuit Module Specifications For 51.8V Li-ion/Li-po Battery Pack

Model: PCM-SM26-14SLI

No.	Test item		Criterion
1	Voltage	Charging voltage	DC: 58.8V CC/CV (4.2V/1cell)
		Balance voltage for single cell	4.20±0.03V
2	Current	Balance current for single cell	85±5mA
		Current consumption for single cell	≤20μA
		Maximal continuous charging current	20A
		Maximal continuous discharging current	25A
3	Over charge Protection (for single cell)	Over charge detection voltage	4.250V±0.025V
		Over charge detection delay time	0.5S—2S
		Over charge release voltage	4.190V±0.05V
4	Over discharge protection (for single cell)	Over discharge detection voltage	2.80±0.05V
		Over discharge detection delay time	100—200mS
		Over discharge release voltage	3.00±0.05V
5	Over current protection	Over current detection voltage	0.15±0.015V
		Over current detection current	100±20A
		Detection delay time	10ms—50ms
		Release condition	Cut load
6	Short protection	Detection condition	Exterior short circuit
		Detection delay time	200-800us
		Release condition	Cut load
7	Resistance	Protection circuitry (B- TO P-)	≤30mΩ
8	Temperature	Operating Temperature Range	-40~+85℃
		Storage Temperature Range	-40~+125℃

L145*W55*T20mm

Charge: P+ and CH-
Discharge: P+ and P-

