

3.65V/40A LiFePO4 Battery Charger

Operating Instructions

Features

- 100V - 240V AC input for worldwide power support.
- Intelligent charger designed for any 3.2V (1 cell) LiFePO4 Battery packs.
- Stabilized output, low ripple.
- Built in cooling fan to ensure charger long service life.
- Safety protection
 - Over Voltage protection
 - Short Circuit protection
- The charger will cut off power automatically if battery is full, and indicate by LED
 - AC Connected/ In charging --- Red LED
 - No Battery Connected/ Battery Fully charged --- Green LED

Specification

- In-put: AC 100 -240V 50/60Hz worldwide power support
- Output: DC 3.65V (CC/CV)
- Charging current: 40A
- Efficiency: >75%
- Operate temperature: $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$

Warning

- Make sure your battery voltage match with your charger.
- Always place the charger in well-ventilated, dry environment and indoor use only.
- Never charge other type batteries except Li-ION/Polymer.
- Subject to change without prior notice, please contact us for the latest information.
- Indoor used only, never expose the charger to water such as rain and splash.
- Make sure good ventilation is provided when charger operation. Never place the charger near radiator, heat register or similar heat source when in charging.

Configuration

