

# Protection Circuit Module Specifications For 11.1V Li-ion/Li-po Battery Pack

Model# CU-JAS317

No.	Test item		Criterion
1	Voltage	Charging voltage	DC: 12.6V CC/CV (4.20V/cell)
		Balance voltage for single cell	
2	Current	Balance current for single cell	
		Current consumption for single cell	≤50 μA
		Maximal continuous discharging current	4A
3	Over charge Protection (single cell)	Over charge detection voltage	4.25V±0.025V
		Over charge detection delay time	0.3S—2S
		Over charge release voltage	4.100V±0.05V
4	Over discharge protection (single cell)	Over discharge detection voltage	3.0V±0.08V
		Over discharge detection delay time	300-2000ms
		Over discharge release voltage	3.2±0.10V
5	Over current protection	Over current detection voltage	0.1±0.025V
		Over current detection current	6±1A
		Detection delay time	30ms-200ms
		Release condition	Cut load
6	Short protection	Detection condition	Exterior short circuit
		Detection delay time	100-600us
		Release condition	Cut load
7	Resistance	Protection circuitry	≤50mΩ
8	Temperature	Operating Temperature Range	-40~+85℃
		Storage Temperature Range	-40~+125℃

L41\*W13\*T3.5mm

P+=Charge+/Discharge+

Size:L41\*W13mm

P- =Charge-/Discharge-

